



## Application of a topological viscosity model to stone wool compositions

Solvang, M.; Kraglund, M.R.; Zheng, Qiuju; Yue, Yuanzheng

*Publication date:*  
2014

*Document Version*  
Accepted author manuscript, peer reviewed version

[Link to publication from Aalborg University](#)

*Citation for published version (APA):*

Solvang, M., Kraglund, M. R., Zheng, Q., & Yue, Y. (2014). *Application of a topological viscosity model to stone wool compositions*. Abstract from 1st Joint Meeting of DGG – ACerS GOMD, Aachen, Germany.

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal -

### Take down policy

If you believe that this document breaches copyright please contact us at [vbn@aub.aau.dk](mailto:vbn@aub.aau.dk) providing details, and we will remove access to the work immediately and investigate your claim.

## Application of a topological viscosity model to stone wool compositions

Mette Solvang<sup>1</sup>, Mikkel Rykær Kraglund<sup>1</sup>, Qiuju Zheng<sup>2</sup> and Yuanzheng Yue<sup>2</sup>

<sup>1</sup>*ROCKWOOL International A/S, Denmark*

<sup>2</sup>*Section of Chemistry, Aalborg University, Denmark*

Shear viscosity is one of the most important technological parameters for both glass and glass fibre production. The operational window, in which the fiberizing is possible, is mainly determined by the viscosity-temperature relationship. It is therefore of great importance to be able to predict this relationship for designing new melt composition for fiberizing in terms of fiber spinnability and working range of temperature. This is especially crucial when working with complex multicomponent liquids since the experimental determination of viscosity is very time and economy demanding. There exist various predictive models for predicting the viscosity-temperature relationship in different composition fields. Recently a topological model for predicting the viscosity of multicomponent compositions has been suggested by Mauro, *et. al.* [1,2]. In this paper, we demonstrate how this model is applied to stone wool compositions. The results show that there is a good agreement between the predicted viscosity-temperature trend and experimental trend. We investigate the influence of individual components for typical stone wool compositions on the melt viscosity at liquidus temperature and hence the melt spinnability. We present a couple of examples showing how a small variation in composition drastically affects the viscosity and hence the fiberizing process.

[1] J. C. Mauro, A.J. Ellison, D. C. Allan, M.M. Smedskjær, “Topological Model for the Viscosity of Multicomponent Glass-Forming Liquids”, *Inter. J. Appl. Glass Sci.* (2012) (in press).

[2] J. C. Mauro, Y. Z. Yue, A. J. Ellison, P. K. Gupta and D. C. Allan: “Viscosity of Glass-forming liquids”, *Proc. Nat. Acad. Sci. USA* 106 (2009) 19780.